



SAFETY DATA SHEET

in accordance with 1907/2006/EC (REACH, as amended by 2015/830/EU) 29 CFR 1910.1200 and WHMIS 2015

Revision date: 29 December 2020

Initial date of issue: 6 July 2007

SDS No. 151A-20c

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

775 Moisture Shield (Aerosol)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Displaces moisture; deposits a clear, protective coating for metals in process, storage, transit, use. Easily removable. This is a solvent base coating.

1.3. Details of the supplier of the safety data sheet

Company:

A.W. CHESTERTON COMPANY
860 Salem Street
Groveland, MA 01834-1507, USA
Tel. +1 978-469-6446 Fax: +1 978-469-6785
(Mon. - Fri. 8:30 - 5:00 PM EST)
SDS requests: www.chesterton.com
E-mail (SDS questions): ProductMSDSs@chesterton.com
E-mail: customer.service@chesterton.com

Supplier:

Canada: A.W. Chesterton Company Ltd., 889 Fraser Drive,
Unit 105, Burlington, Ontario L7L 4X8 - Tel. 905-335-5055
EU: Chesterton International GmbH, Am Lenzenfleck 23,
D85737 Ismaning, Germany – Tel. +49-89-996-5460

1.4. Emergency telephone number

24 hours per day, 7 days per week
Call Infotrac: 1-800-535-5053
Outside N. America: +1 352-323-3500 (collect)
NSW Poisons Information Centre (Australia): 13 11 26

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

2.1.1. Classification according to Regulation (EC) No 1272/2008 [CLP]

Aerosol 1, H222, H229
Skin Irrit. 2, H315
STOT SE 3, H336
Aquatic Chronic 2, H411

2.1.2. Classification according to 29 CFR 1910.1200 / WHMIS 2015

Flam. Aerosol 1, H222
Press. Gas (Comp.), H280
Skin Irrit. 2, H315
STOT SE 3, H336
Aquatic Chronic 2, H411

2.1.3. Australian statement of hazardous nature

Hazardous according to criteria of Safe Work Australia.

2.1.4. Additional information

For full text of H-statements: see SECTIONS 2.2 and 16.

2.2. Label elements**2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]****Hazard pictograms:****Signal word:** Danger

Hazard statements: H222 Extremely flammable aerosol.
 H229 Pressurized container: May burst if heated.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing vapours/spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves and eye protection.
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.
 P410/412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Supplemental information: None**2.2.2. Labelling according to 29 CFR 1910.1200 / WHMIS 2015****Hazard pictograms:****Signal word:** Danger

Hazard statements: H222 Extremely flammable aerosol.
 H280 Contains gas under pressure; may explode if heated.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing vapours/spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves and eye protection.
 P302/352 IF ON SKIN: Wash with plenty of soap and water.
 P304/340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.
 P332/313 If skin irritation occurs: Get medical advice/attention.
 P362/364 Take off contaminated clothing and wash it before reuse.
 P403 Store in a well-ventilated place.
 P410/412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container to an approved waste disposal plant.

Supplemental information: None**2.3. Other hazards**

None

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures**

Hazardous Ingredients ¹	% Wt.	CAS No./ EC No.	REACH Reg. No.	CLP/GHS Classification
Distillates (petroleum), hydrotreated light	75-85	64742-47-8 265-149-8	NA	Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411 Acute Tox. 4, H302/H332
Hydrocarbon Waxes (Petroleum), Oxidized, Me Esters, Barium Salts	5-7	68603-10-1 271-637-1	NA	Acute Tox. 4, H302/H332
Benzenesulfonic acid, di-C10-18-alkyl derivs., barium salts	3-6	93820-55-4 298-635-3	NA	Press. Gas (Comp.), H280
Carbon dioxide	1-5	124-38-9 204-696-9	NA	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated heavy naphthenic*	5-10	64742-52-5 265-155-0	NA	

For full text of H-statements: see SECTION 16.

*Contains less than 3 % DMSO extract as measured by IP 346.

¹ Classified according to: * 29 CFR 1910.1200, 1915, 1916, 1917, Mass. Right-to-Know Law (ch. 40, M.G.L..O. 111F), California Proposition 65
* 1272/2008/EC, GHS, REACH
* WHMIS 2015
* Safe Work Australia

SECTION 4: FIRST AID MEASURES**4.1. Description of first aid measures**

Inhalation: Remove to fresh air. If not breathing, administer artificial respiration. Contact physician immediately.

Skin contact: Wash skin with soap and water. Take off contaminated clothing and wash it before reuse. Contact physician if irritation persists.

Eye contact: Flush eyes for at least 15 minutes with large amounts of water. Contact physician if irritation persists.

Ingestion: Do not induce vomiting. Contact physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Direct contact may cause mild eye irritation. Inhalation of excessive vapors may result in irritation of the eyes and respiratory tract, dizziness, headache and other central nervous system effects. Prolonged or repeated skin contact may defat the skin and cause skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: FIREFIGHTING MEASURES**5.1. Extinguishing media**

Suitable extinguishing media: Carbon dioxide, dry chemical, foam or water spray

Unsuitable extinguishing media: High volume water jet

5.2. Special hazards arising from the substance or mixture

Pressurized containers, when heated, are a potential explosive hazard.

5.3. Advice for firefighters

Cool exposed containers with water. Recommend Firefighters wear self-contained breathing apparatus.

Flammability Classification: –

HAZCHEM Emergency Action Code: 2 Y

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Provide adequate ventilation. Utilize exposure controls and personal protection as specified in Section 8.

6.2. Environmental Precautions

Keep out of sewers, streams and waterways.

6.3. Methods and material for containment and cleaning up

Contain spill to a small area. Pick up with absorbent material (sand, sawdust, clay, etc.) and place in a suitable container for disposal. Keep away from sources of ignition - No smoking. If removal of ignition sources is not possible, then flush material away with water.

6.4. Reference to other sections

Refer to section 13 for disposal advice.

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for safe handling**

Vapors are heavier than air and will collect in low areas. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No Smoking.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C (120°F). Do not pierce or burn, even after use.

7.3. Specific end use(s)

No special precautions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limit values**

Ingredients	OSHA PEL ¹		ACGIH TLV ²		UK WEL ³		AUSTRALIA ES ⁴	
	ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Distillates (petroleum), hydrotreated light	–	–	179*	1200*	–	–	–	–
Hydrocarbon Waxes (Petroleum), Oxidized, Me Esters, Barium Salts	–	–	–	–	–	–	–	–
Benzenesulfonic acid, di-C10-18-alkyl derivs., barium salts	–	–	–	–	–	–	–	–
Carbon dioxide	5000	9000	5000 STEL: 30000	9000 54000	5000 STEL: 15000	9150 27400	5000 STEL: 30000	9000 54000
Oil mist, mineral	–	5	(inhal)	5	–	–	–	5

*Based on the procedure described in appendix H, "Reciprocal calculation method for Certain Refined Hydrocarbon Solvent Vapor Mixtures" of the ACGIH TLVs® and BEIs®.

¹ United States Occupational Health & Safety Administration permissible exposure limits

² American Conference of Governmental Industrial Hygienists threshold limit values

³ EH40 Workplace exposure limits, Health & Safety Executive

⁴ Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003]

Derived No Effect Level (DNEL) according to Regulation (EC) No 1907/2006:**Workers**

Not available

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No 1907/2006:

Not available

8.2. Exposure controls**8.2.1. Engineering measures**

No special requirements. If exposure limits are exceeded, provide adequate ventilation.

8.2.2. Individual protection measures

Respiratory protection: Not normally needed. If exposure limits are exceeded, use approved organic vapor respirator (e.g., EN filter type A-P3, half mask).

Protective gloves: Chemical resistant gloves (e.g., rubber, nitrile)
Eye and face protection: Safety goggles or glasses.
Other: Impervious clothing as necessary for repetitive, prolonged skin contact.

8.2.3. Environmental exposure controls

Refer to sections 6 and 12.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	liquid	Odour	mild petroleum odor
Colour	amber	Odour threshold	not determined
Initial boiling point	207°C (405°F), product only	Vapour pressure @ 20°C	not determined
Melting point	not determined	% Aromatics by weight	not known
% Volatile (by volume)	82%	pH	–
Flash point	66°C (150°F), product only	Relative density	0.8 kg/l
Method	PM Closed Cup	Weight per volume	6.73 lbs/gal.
Viscosity	not determined	Coefficient (water/oil)	< 1
Autoignition temperature	not determined	Vapour density (air=1)	> 1
Decomposition temperature	not determined	Rate of evaporation (ether=1)	< 1
Upper/lower flammability or explosive limits	not determined	Solubility in water	insoluble
Flammability (solid, gas)	not applicable	Oxidising properties	not applicable
Explosive properties	not applicable		

9.2. Other information

None

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Refer to sections 10.3 and 10.5.

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No dangerous reactions known under conditions of normal use.

10.4. Conditions to avoid

Open flames, heat, sparks and red hot surfaces.

10.5. Incompatible materials

Strong oxidizers like liquid Chlorine and concentrated Oxygen.

10.6. Hazardous decomposition products

Carbon Monoxide, aldehydes and other toxic fumes.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Primary route of exposure under normal use: Inhalation, skin and eye contact. Personnel with pre-existing dermatitis are generally aggravated by exposure.

Acute toxicity -

Oral: ATE-mix > 5000 mg/kg.

Substance	Test	Result
Distillates (petroleum), hydrotreated light	LD50, rat	> 5000 mg/kg
Distillates (petroleum), hydrotreated heavy naphthenic	LD50 rat	> 5000 mg/kg, estimated

Dermal:

Substance	Test	Result
Distillates (petroleum), hydrotreated light	LD50, rabbit	> 2000 mg/kg
Distillates (petroleum), hydrotreated heavy naphthenic	LD50, rabbit	> 2000 mg/kg, estimated

Inhalation:

ATE-mix > 5 mg/l, mist. Inhalation of excessive vapors may result in irritation of the eyes and respiratory tract, dizziness, headache and other central nervous system effects.

Substance	Test	Result
Distillates (petroleum), hydrotreated light	LC50, rat, 4 hours	> 5.2 mg/l
Distillates (petroleum), hydrotreated heavy naphthenic	LC50, rat, 4 hours	> 5 mg/l, estimated

Skin corrosion/irritation:

Prolonged or repeated skin contact may defat the skin and cause skin irritation.

Substance	Test	Result
Distillates (petroleum), hydrotreated light	Skin irritation, rabbit	Slightly irritating / Moderately irritating
Distillates (petroleum), hydrotreated heavy naphthenic	Skin irritation, rabbit	Not irritating

Serious eye damage/irritation:

Direct contact may cause mild eye irritation.

Substance	Test	Result
Distillates (petroleum), hydrotreated light	Eye irritation, rabbit	Not irritating / Slightly irritating
Distillates (petroleum), hydrotreated heavy naphthenic	Eye irritation, rabbit	Not irritating

Respiratory or skin sensitisation:

Substance	Test	Result
Distillates (petroleum), hydrotreated light	Skin sensitization, guinea pig	Not sensitizing
Distillates (petroleum), hydrotreated heavy naphthenic	Skin sensitization, (OECD 406), guinea pig	Not sensitizing

Germ cell mutagenicity:

Distillates (petroleum), hydrotreated light, Distillates (petroleum), hydrotreated heavy naphthenic: based on available data, the classification criteria are not met.

Carcinogenicity:

As per 29 CFR 1910.1200 (Hazard Communication), this product contains no carcinogens as listed by the National Toxicology Program (NTP), the International Agency for Research on Cancer (IARC), the Occupational Safety and Health Administration (OSHA) or Regulation (EC) No 1272/2008.

Reproductive toxicity:

Distillates (petroleum), hydrotreated light, Distillates (petroleum), hydrotreated heavy naphthenic: based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure:

Distillates (petroleum), hydrotreated light, Distillates (petroleum), hydrotreated heavy naphthenic: based on available data, the classification criteria are not met.

Aspiration hazard:

Not classified as an aspiration toxicant due to the aerosol spray pattern.

Other information:

None known

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. The information given below is based on a knowledge of the components and the ecotoxicology of similar substances.

12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

Distillates (petroleum), hydrotreated light: can degrade in air; inherently biodegradable. Distillates (petroleum), hydrotreated naphthenic: not readily biodegradable (biodegradation, OECD 301F, 28 days: 31%).

12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated light: Octanol/water partition coefficient (log Kow) = 2.1-6.5. Distillates (petroleum), hydrotreated naphthenic: not expected to bioaccumulate.

12.4. Mobility in soil

Liquid. Insoluble in water. In determining environmental mobility, consider the product's physical and chemical properties (see Section 9). Distillates (petroleum), hydrotreated light: will rapidly evaporate to the air if released into the environment.

12.5. Results of PBT and vPvB assessment

Not available

12.6. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS**13.1. Waste treatment methods**

Incinerate absorbed material with a properly licensed facility. Treatment standards for Barium may need to be met prior to land disposal. Incinerate pressurized or sealed containers in an approved facility. Check local, state and national/federal regulations and comply with the most stringent requirement. This product is classified as a hazardous waste according to 2008/98/EC.

SECTION 14: TRANSPORT INFORMATION**14.1. UN number**

ADR/RID/ADN/IMDG/ICAO:	UN1950
TDG:	UN1950
US DOT:	UN1950

14.2. UN proper shipping name

ICAO:	Aerosols, Flammable
IMDG:	Aerosols
ADR/RID/ADN:	Aerosols, <i>flammable</i>
TDG:	Aerosols, <i>flammable</i>
US DOT:	Aerosols, <i>flammable</i>

14.3. Transport hazard class(es)

ADR/RID/ADN/IMDG/ICAO:	2.1
TDG:	2.1
US DOT:	2.1

14.4. Packing group

ADR/RID/ADN/IMDG/ICAO:	NOT APPLICABLE
TDG:	NOT APPLICABLE
US DOT:	NOT APPLICABLE

14.5. Environmental hazards

NO ENVIRONMENTAL HAZARDS

14.6. Special precautions for user

NO SPECIAL PRECAUTIONS FOR USER

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

NOT APPLICABLE

14.8. Other information

US DOT: Shipped as Limited Quantity in packaging having a rated capacity gross weight of 66 lb. or less (49 CFR 173.306(a),(3),(i)). ERG NO. 126

IMDG: EmS. F-D, S-U, Shipped as Limited Quantity

ADR: Classification code 5F, Tunnel restriction code (E), Shipped as Limited Quantity

SECTION 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.1.1. EU regulations**

Authorisations under Title VII: Not applicable

Restrictions under Title VIII: None

Other EU regulations: Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers. Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances. Directive 94/33/EC on the protection of young people at work.

15.1.2. National regulations

US EPA SARA TITLE III

312 Hazards: **313 Chemicals:**
Barium Compounds 8-12%

Other national regulations: National implementations of the EC Directives referred to in section 15.1.1.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION

Abbreviations and acronyms: ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE: Acute Toxicity Estimate
BCF: Bioconcentration Factor
cATpE: Converted Acute Toxicity point Estimate
CLP: Classification Labelling Packaging Regulation (1272/2008/EC)
ES: Exposure Standard
GHS: Globally Harmonized System
ICAO: International Civil Aviation Organization
IMDG: International Maritime Dangerous Goods
LC50: Lethal Concentration to 50 % of a test population
LD50: Lethal Dose to 50% of a test population
LOEL: Lowest Observed Effect Level
N/A: Not Applicable
NA: Not Available
NOEC: No Observed Effect Concentration
NOEL: No Observed Effect Level
OECD: Organization for Economic Co-operation and Development
PBT: Persistent, Bioaccumulative and Toxic substance
(Q)SAR: Quantitative Structure-Activity Relationship
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (1907/2006/EC)
REL: Recommended Exposure Limit
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS: Safety Data Sheet
STEL: Short Term Exposure Limit
STOT RE: Specific Target Organ Toxicity, Repeated Exposure
STOT SE: Specific Target Organ Toxicity, Single Exposure
TDG: Transportation of Dangerous Goods (Canada)
TWA: Time Weighted Average
US DOT: United States Department of Transportation
vPvB: very Persistent and very Bioaccumulative substance
WEL: Workplace Exposure Limit
WHMIS: Workplace Hazardous Materials Information System
Other abbreviations and acronyms can be looked up at www.wikipedia.org.

Key literature references and sources for data: Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST)
Chemical Classification and Information Database (CCID)
European Chemicals Agency (ECHA) - Information on Chemicals
Hazardous Chemical Information System (HCIS)
National Institute of Technology and Evaluation (NITE)
Swedish Chemicals Agency (KEMI)
U.S. National Library of Medicine Toxicology Data Network (TOXNET)

Procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008 [CLP]:

Classification	Classification procedure
Aerosol 1, H222	On basis of components
STOT SE 3, H336	Bridging principle "Dilution"
Skin Irrit. 2, H315	Calculation method
Aquatic Chronic 2, H411	Calculation method

Relevant H-statements: H222: Extremely flammable aerosol.
 H280: Contains gas under pressure; may explode if heated.
 H302: Harmful if swallowed.
 H304: May be fatal if swallowed and enters airways.
 H315: Causes skin irritation.
 H332: Harmful if inhaled.
 H336: May cause drowsiness or dizziness.
 H411: Toxic to aquatic life with long lasting effects.

Hazard pictogram names: Flame, gas cylinder (non-CLP labelling) exclamation mark, environment

Changes to the SDS in this revision: Section 14.8.

Revision date: 29 December 2020

Further information: None

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself. No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose. The user must make their own determination as to suitability.