



250

DUAL CARTRIDGE SEAL

FOR GENERAL INDUSTRIAL APPLICATIONS



GENERAL INDUSTRIAL SEALING

250

SIMPLE, RELIABLE, AND AFFORDABLE

Chesterton's 250 dual cartridge seal is a value leader in its class. With proven Chesterton quality, it is the ideal choice for increasing seal performance when your current sealing method is not meeting expectations.



The 250 dual seal provides sealing security that conventional single seals cannot match. A durable secondary seal provides the opportunity for scheduled maintenance, thereby avoiding unplanned downtime and production losses.

Advantages of upgrading to the 250 preassembled dual cartridge design:

- Provides clean barrier fluid for seal face lubrication
- Improves cooling for higher temperature applications
- Increases seal life with a proven, double balanced design
- Eliminates leakage associated with single seal failures




4



The 250 dual cartridge seal is the economical solution to meet the needs of today's industry.

- Constructed of high quality materials
- Fits popular ANSI/ISO and vertical pumps
- Fast and easy installation
- Field and factory repairability
- Worldwide, off-the-shelf availability



1 Installs Easily and Accurately

Multi-directional centering clips automatically position the seal and set consistent spring pressure.

2 Enhances Circulation

The gland design produces increased barrier fluid flow, providing better cooling capability. This is beneficial in installations using barrier fluid tanks.

3 Avoids Clogging

Multi-coiled springs provide even, consistent face load, and are placed out of the sealing fluid to avoid clogging.

4 Enhanced Torque Capabilities

Heavy-duty drive lugs reduce wear damage and handle higher starting torque.

5 Optimized Seal Face Geometrics

Through finite element analysis, the composite seal face design is optimized to improve lubrication and extend seal life.

6 Durable, Balanced Design

Double balance provides improved sealing performance when pressure fluctuations occur.

Standard Offerings

Size Range	1" (25mm) – 4.75" (120mm)
Hardware	316 Stainless Steel
Seal Face Combination	CB/SSC/SSC/CB SSC/SSC/SSC/CB
O-Rings	EP, FKM, and Aflas™ as standard Chemlast™ available upon request

Operating Parameters

Operating Speed	Up to 3600 RPM
Pressure Rating*	Vacuum to 300 Psig (20 bar g) process pressure 150 Psig (10 bar g) maximum barrier pressure
Temperature	-20°F to 400°F (-30°C to 200°C)

*Seal pressure capabilities are dependent on the fluid sealed, temperature, speed, and seal face combinations.



GLOBAL SOLUTIONS, LOCAL SERVICE

Since 1884, Chesterton has been providing value driven solutions to meet industry's needs. Chesterton solutions have been implemented around the world with documented success and recognition. Increasing equipment reliability, optimizing energy consumption, and providing local technical support and service are what Chesterton offers industry worldwide.

- Servicing Plants in Over 100 Countries
- Global Manufacturing Operations
- Over 500 Service Centers and Sales Offices Worldwide
- Over 1200 Trained Local Service Specialists and Technicians

Visit our website at
www.chesterton.com

ISO certifications available on www.chesterton.com/corporate/iso

Aflas is a registered trademark of Asahi Glass Company Ltd.
Technical data reflects results of laboratory tests and is intended to indicate general characteristics only.
A.W. CHESTERTON CO. DISCLAIMS ALL WARRANTIES EXPRESSED, OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE OR USE. LIABILITY, IF ANY, IS LIMITED TO PRODUCT REPLACEMENT ONLY.



DISTRIBUTED BY:

860 Salem Street
Groveland, MA 01834 USA
Telephone: 781-438-7000
Fax: 978-469-6528
www.chesterton.com

© A.W. Chesterton Company, 2007. All rights reserved.
® Registered trademark owned and licensed by
A.W. Chesterton Company in USA and other countries.

FORM NO. 088838

PRINTED IN USA 5/07